



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/684,490	10/04/2000	David C. Gelvin	SENS.P010	3128

33717 7590 02/05/2007
GREENBERG TRAURIG LLP
2450 COLORADO AVENUE, SUITE 400E
SANTA MONICA, CA 90404

EXAMINER

JACOBS, LASHONDA T

ART UNIT	PAPER NUMBER
----------	--------------

2157

SHORTENED STATUTORY PERIOD OF RESPONSE	MAIL DATE	DELIVERY MODE
3 MONTHS	02/05/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

Office Action Summary	Application No. 09/684,490	Applicant(s) GELVIN ET AL.	
	Examiner LaShonda T. Jacobs	Art Unit 2157	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
 - If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
 - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
 - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
- Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 25 October 2006.
- 2a) ☒ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-9, 12-15, 17, 20-67, 69-74 and 76-85 is/are pending in the application.
- 4a) Of the above claim(s) 20 and 21 is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-9, 12-15, 17, 22-67, 69-74 and 76-85 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Response to Amendment

This is a Final Office Action in response to Applicants' Amendment/Request for Reconsideration filed on October 25, 2006. Applicants newly add claims 77-85. Claims 1-9, 12-15, 22-67, 69-74 and 76 are presented for further examination. Claims 77-85 are also presented for examination.

Claim Rejections - 35 USC § 103

1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

2. Claims 1-9, 12-15, 22-67, 69-74, 76-77 and 85 are rejected under 35 U.S.C. 103(a) as being unpatentable over Jones et al (hereinafter, "Jones", 6,430,164) in view of Lu et al (hereinafter, "Lu", U.S. Pat. No. 5,734,699).

As per claims 1, 77 and 85, Jones discloses a mobile internetwork comprising:

- a plurality of network elements including at least one gateway node and at least one local area network coupled among at least one peripheral electronic device, wherein functions of the plurality of network elements are remotely controllable, wherein the at least one node manipulates node information including configuration and security information to provide secure interoperability among the plurality of network elements

and the at least one peripheral electronic device, (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-4, lines 54-67, col. 6, lines 1-16 and col. 18, lines 41-45);

- wherein the gateway node provides at least one of data processing, data storage, access control, protocol translation, security including service discovery and device authentication and network control (col. 18, lines 17-22 and lines 42-51; Jones discloses that the communication apparatus can also be configured as a gateway to provide data logging/reduction, vehicle diagnostics, etc. Therefore, Jones does disclose a gateway node that provides at least one of data processing, data storage, access control, protocol translation, security including service discovery and device authentication and network control), wherein the gateway node controls remote access to the mobile internetwork in response to intermittent external communications (col. 18, lines 42-51).

However, Jones does not explicitly disclose:

- wherein the gateway node comprises at least one interface port, at least one real-time interface processor (RTIP), and at least one application processor, wherein the at least one RTIP performs real-time operations and at least one application processor performs high level processing function.

In an analogous art, Lu discloses a cellular private branch exchanges for facilitating cellular communications comprising:

- wherein the gateway node comprises at least one interface port, at least one real-time interface processor (RTIP), and at least one application processor, wherein the at least one RTIP performs real-time operations and at least one application processor performs high level processing function (col. 20, lines 50-62 and col. 21, lines 44-60).

Given the teaching of LU, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Jones by including a real-time processor to process real-time information and communicate control information over a VEM bus thereby providing a system capable of providing and processing real-time information in a timely and efficient manner.

As per claim 2, Jones discloses:

- wherein the at least one local area network comprises at least one of an Original Equipment Manufacturer (OEM) bus, an AutomotiveMultimedia Interface Consortium (AMI-C) bus, at least one external network, and at least one local development network (col. 4, lines 49-67, and col. 5, lines 1-4).

As per claim 3, Jones discloses:

- wherein the at least one local development network accesses the at least one gateway node for the performance of application upgrades, diagnostics, and programming (abstract, col. 2, lines 1-49 and col. 18, lines 41-45).

As per claim 4, Jones discloses:

- wherein the at least one local development network supports manipulation and transfer of entertainment software, wherein the entertainment software comprises at least one entertainment feature including video, audio, movies, television shows, music, games, and simulations (col. 2, lines 1-49 and col. 5, lines 15-53).

As per claim 5, Jones discloses:

- wherein the at least one vehicle bus comprises at least one legacy automotive bus including at least one of Audio Control Protocol (ACP) buses and Standard Corporate Protocol (SCP) buses (col. 4, lines 49-67 and col. 5, lines 1-4).

As per claim 6, Jones discloses:

- wherein the at least one peripheral electronic device comprises at least one device coupled to at least one OEM bus wherein the device includes at least one of climate control devices, actuator devices, position location devices, Global Positioning System (GPS) devices, communication devices, cellular telephony devices, processing devices, diagnostic devices, modems, video devices, audio devices, multimedia devices, electronic game devices, sensor devices, switch devices, and device subnetworks (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54 and col. 6, lines 1-16).

As per claim 7, Jones discloses:

- wherein the at least one peripheral electronic device comprises at least one device coupled to at least one AMI-C bus including communication devices, position location devices, GPS devices, communication devices, pager devices, cellular telephony devices, processing devices, modems, video devices, audio devices, multimedia devices, electronic game devices, personal digital assistants (PDAs), and wireless local area network (LAN) devices (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54 and col. 6, lines 1-16).

As per claim 8, Jones discloses:

- wherein the at least one node comprises at least one interface port that is at least one of Intelligent Data Bus (IDB-C) ports, MOST ports, Institute of Electrical and Electronics

Engineers (IEEE) 1394 ports, On-Board Diagnostic-11 (OBD-II) ports, Standard Corporate Protocol (SCP) ports, Audio Control Protocol (ACP) ports, Bluetooth ports, Personal Communications Service (PCS) ports, Global System for Mobile Communications (GSM) ports, and Ethernet ports (abstract, col. 2, lines 1-25, col. 4, lines 49-67 and col. 5, lines 1-4).

As per claim 9, Jones discloses:

- wherein the functions are hosted on a central network element, wherein the functions are distributed among the plurality of network elements in response to a coupling of additional peripheral electronic devices to the at least one vehicle bus (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-67 and col. 6, lines 1-16).

As per claim 12, Jones discloses:

- wherein the at least one gateway node functions as Internet Protocol (IP) router, wherein the at least one RTIP comprises a high speed bus controlled by at least one coupled device (abstract, col. 2, lines 1-25, col. 4, lines 49-67 and col. 18, lines 41-45).

As per claim 13, Jones discloses:

- wherein the at least one interface port has at least one function that includes at least one of a tag, a bridge, and an interface (col. 17, line 67 and col. 18, lines 1-55).

As per claim 14, Jones discloses:

- wherein the at least one interface port includes at least of wired communication ports and wireless communication ports (col. 17, line 67 and col. 18, lines 1-55).

As per claim 15, Jones discloses:

Art Unit: 2157

- wherein the at least one gateway node includes a first gateway coupled to a second gateway (col. 17, line 67 and col. 18, lines 1-55).

As per claim 17, Jones discloses:

- wherein the at least one gateway node couples a first vehicle bus and a second vehicle bus, wherein the at least one interface port couples the at least one vehicle bus to the at least one peripheral electronic device (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67 and col. 18, lines 1-55).

As per claim 22, Jones discloses:

- wherein the at least one gateway node comprises at least one hybrid switch, wherein the at least one hybrid switch includes at least one interface port coupled among at least one switch of a first speed and at least one switch of a second speed, wherein each of the at least one switch of a first speed and the at least one switch of a second speed are coupled to at least one port (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim 23, Jones discloses:

- wherein the at least one hybrid switch distributes at least one switching function among the plurality of network elements of a host vehicle (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim 24, Jones discloses:

- wherein at least one application of a first type is coupled through the interface port to the at least one switch of a first speed, wherein at least one application of a second type

is coupled through the interface port to the at least: one switch of a second speed
(abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col.
17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **25**, Jones discloses:

- wherein the at least one gateway node couples to at least one subnetwork, wherein the at least one subnetwork comprises at least one of sensor devices, actuator devices, wired network devices, and wireless network devices (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **26**, Jones further discloses:

- at least one router that couples to the Internet using at least one bus and at least one communication device, wherein the at least one bus includes at least one of an IEEE 1394 bus, a MOST bus, an 11313-C bus, and an Ethernet bus, wherein the at least one communication device includes at least one of a Bluetooth modem, an IEEE 802.11 radio, and a mobile telephone (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **27**, Jones discloses:

- wherein the at least one gateway node generates at least one hierarchy of communication alternatives in response to a determined position of a host vehicle, wherein a selected communication alternative is used to communicate with at least one

Art Unit: 2157

local site (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **28**, Jones discloses:

- wherein data processing is controlled using at least one processing hierarchy that controls at least one event including at least one of data classifications, data transfers, data queuing, data combining, processing locations, and communications among the plurality of network elements (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **29**, Jones discloses:

- wherein the functions are distributed among the plurality of network elements (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **30**, Jones discloses:

- wherein the functions of the at least one gateway node include at least one of data acquisition, data processing, communication management, data routing, data security, programming, node operation, protocol translation, network management, and interfacing with at least one communication physical layer including cellular telephony, wireline telephone, satellite telephony, packet radio, microwave, optical (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **31**, Jones discloses:

- wherein data processing functions of the peripheral electronic device are distributed among at least one other processor that includes a processor of the at least one node and the at least one peripheral electronic device (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **32**, Jones discloses:

- wherein the at least one gateway node implements at least one security method that includes at least one of confounder codes, encrypted transmissions, security policy-based communication protocols, blocking coupling with unauthorized devices, and blocking commands from at least one class of device (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **33**, Jones discloses:

- wherein the at least one security method is implemented in at least one gateway node and at least one port node (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **34**, Jones discloses:

- wherein the at least one security method includes blocking denial of service attacks by decoupling at least one interface port through which unauthorized access is attempted and blocking at least one application at a decoupled interface port (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **35**, Jones discloses:

- wherein the at least one security method further includes at least one of a key, a password device, and a security display (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **36**, Jones discloses:

- wherein the at least one security method further includes a designated authorization port, wherein at least one connector is coupled to the designated authorization port to receive authorization for coupling a device to the plurality of network elements (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **37**, Jones discloses:

- wherein the plurality of network elements automatically organize in response to the node information, wherein the automatic organizing comprises automatically controlling data transfer, processing and storage among the plurality of network elements (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **38**, Jones discloses:

- wherein at least one level of synchronization is supported among different subsets of the plurality of network elements, wherein a first level of synchronization is supported among a first subset of the plurality of network elements, wherein a second level of synchronization is supported among a second subset of the plurality of network

elements (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **39**, Jones discloses:

- wherein the plurality of network elements are self-assembling, wherein search and acquisition modes of the at least one gateway node search for participating ones of the plurality of network elements, wherein a determination is made whether each of the participating ones of the plurality of network elements are permitted to join the vehicle internetwork using a message hierarchy, wherein the plurality of network elements are surveyed at random intervals for new nodes and missing nodes (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **40**, Jones discloses:

- wherein the plurality of network elements are self-assembled into a multi-cluster network, wherein a start node is selected as a base node, wherein the base node communicates an assembly packet throughout the vehicle inter-network, wherein information of the assembly packet alternates with each successive communication between directing a node to become a base node of a particular cluster number and directing a node to become a remote node of a particular cluster number, wherein the particular cluster number is incrementally changed with each successive communication of the assembly packet (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **41**, Jones discloses:

- wherein the at least one gateway node performs service discovery that comprises synchronizing gateway node, authenticating the gateway node, determining at least one communication mode for the at least one gateway node, and informing the gateway node of resources available among the plurality of network elements (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **42**, Jones discloses:

- wherein data is collected by the gateway node, wherein at least one operation is performed on the data in response to parameters established by a user, the at least one operation including at least one of classification, routing, processing, storing, and fusing (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **43**, Jones discloses:

- wherein the data is vehicle diagnostic data, wherein diagnostic operations are performed in response to the data (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **44**, Jones discloses:

- wherein routing comprises selecting at least one communication type and at least one communication coupling for use in routing the collected data (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **45**, Jones discloses:

- wherein routing comprises selecting at least one data type for routing, selecting at least one of the plurality of network elements to which to route the selected data, selecting at least one route to the selected network element and routing the selected at least one data type to the selected at least one of the plurality of network elements (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim 46, Jones discloses:

- wherein processing comprises selecting at least one data type for processing, selecting at least one processing type, selecting at least one of the network elements to perform the selected processing type, and transferring data of the selected data type to the selected network elements using at least one route through the network (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67; col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim 47, Jones discloses:

- wherein data processed in a plurality of nodes is aggregated for further processing by other nodes (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim 48, Jones discloses:

- wherein data processed by the at least one gateway node is aggregated for reporting to at least one user (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim 49, Jones discloses:

Art Unit: 2157

- wherein storing comprises selecting at least one data type for storage, selecting at least one storage type, selecting at least one of the network elements to perform the selected at least one storage type, and transferring data of the selected data type to the selected network elements using at least one route through the plurality of network elements (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **50**, Jones discloses:

- wherein fusing comprises a first node transmitting at least one query request to at least one other node, wherein the first node collects data from the at least one other node in response to the at least one query request, and processes the collected data (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **51**, Jones discloses:

- wherein the plurality of network elements comprise a plurality of application programming interfaces (APIs), wherein the APIs include APIs for at least one of application support, database services, routing, security, network management, and deployment (col. 9, lines 51-67 and col. 10, lines 1-57).

As per claim **52**, Jones discloses:

- wherein the APIs for application support, database services, and routing are hosted on at least one gateway node, wherein the APIs for security, network management, and deployment are shared among at least one other gateway node and at least one port node (col. 9, lines 51-67 and col. 10, lines 1-57).

As per claim **53**, Jones discloses:

- wherein the plurality of APIs are layered, wherein the plurality of APIs enable distributed resource management by providing network resource information among the plurality of network elements, wherein information transfer among the plurality of network elements is controlled using a synchronism hierarchy established in response to the network resource information (col. 9, lines 51-67, col. 10, lines 1-57 and col. 11, lines 45-67).

As per claim **54**, Jones discloses:

- wherein the plurality of network elements support atomic transaction methods (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **55**, Jones discloses:

- wherein the at least one gateway node includes sensing, processing, communications, and storage devices supporting a plurality of processing and protocol layers (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **56**, Jones discloses:

- wherein the at least one gateway node supports at least one of wireless communications modes, wired communications modes, and hybrid wired and wireless communications modes (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **57**, Jones discloses:

- wherein the at least one gateway node is coupled to the at least one remote computer using the plurality of network elements, wherein the plurality of network elements includes at least one of at least one station gateway, at least one server, at least one repeater, at least one interrogator, and at least one network, wherein the at least one network includes wired networks, wireless networks, and hybrid wired and wireless networks (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **58**, Jones discloses:

- wherein the at least one network comprises at least one of the Internet, local area networks, wide area networks, metropolitan area networks, and information service stations (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **59**, Jones discloses:

- wherein the plurality of network elements provides remote accessibility using World Wide Web-based tools to data, code, control, and security functions, wherein data includes signals, wherein code includes signal processing, decision support, and database elements, and wherein control includes operation of the plurality of network elements (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **60**, Jones discloses:

- wherein the plurality of network elements comprise a plurality of network element sets, wherein the plurality of network element sets are layered (abstract, col. 2, lines 1-25,

Art Unit: 2157

col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **61**, Jones discloses:

- wherein the gateway node comprises a plurality of node types that includes at least one node of a first type and at least one node of a second type, wherein a first network having a first node density is assembled using the at least one node of a first type, wherein a second network having a second node density is assembled using the at least one node of a second type, wherein the second network is overlaid onto the first network (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **62**, Jones discloses:

- wherein software and data are transferable among the plurality of network elements, wherein the transfer is remotely controllable, wherein the software and the data are downloadable from at least one location selected from a group consisting of storage devices of the plurality of network elements, external storage devices, and remote storage devices (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **63**, Jones discloses:

- wherein the plurality of network elements are managed as a distributed and active database using a distributed resource management protocol, wherein the plurality of network elements are reused among different applications, wherein the network elements are used in multiple classes of applications (abstract, col. 2, lines 1-25, col. 4,

lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **64**, Jones further discloses:

- at least one database, wherein the at least one database includes at least one of storage devices coupled to at least one of the plurality of network elements and storage devices of the at least one gateway node (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **65**, Jones discloses:

- wherein at least one coupling among the one gateway node and at least one external network supports data transfer among one gateway node of a host vehicle, wherein the data includes vehicle service data, diagnostic data, maintenance history data, security data, electronic mail, and entertainment software (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **66**, Jones discloses:

- wherein at least one coupling among the at least one peripheral electronic device and at least one external network supports data transfer among the gateway node of a host vehicle, wherein the data includes vehicle service data, diagnostic data, maintenance history data, security data, electronic mail, and entertainment software (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **67**, Jones discloses:

- wherein the at least one gateway node is coupled to at least one diagnostic device of a host vehicle (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **69**, Jones discloses:

- wherein the gateway node manipulates at least one vehicle assembly data, vehicle maintenance data, vehicle diagnostics data, vehicle position data, vehicle operations profile data, fleet management data, fleet reliability analysis data, security system data, entertainment system data, and targeted advertising data (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **70**, Jones discloses:

- wherein at least one subset of the plurality of network elements comprise at least one sensor network, wherein the at least one subset further includes at least one sensor node, at least one gateway station, at least one server, at least one gateway network, and at least one client computer hosting a World Wide Web browser, wherein the at least one node is configured as the at least one gateway station and the at least one sensor node (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **71**, Jones discloses:

- wherein the at least one sensor node is coupled among a monitored environment and the at least one client computer, wherein functions of the at least one sensor node are

remotely controllable using the at least one client computer, wherein the at least one sensor node provides the node information including node resource cost and message priority to the plurality of network elements, wherein data processing is distributed among the plurality of network elements in response to the node information (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **72**, Jones discloses:

- wherein at least one redundant communication pathway is established among the plurality of network elements (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **73**, Jones discloses:

- wherein the at least one gateway station performs at least one of protocol translation, sensor network management, management of transmissions from a remote user, and interfacing with at least one communication physical layer including wired local area networks, packet radio, microwave, optical, wireline telephony, cellular telephony, and satellite telephony (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim **74**, Jones discloses:

- wherein the at least one gateway network includes wired networks, wireless networks, and hybrid wired and wireless networks, wherein the at least one gateway network comprises at least one of the Internet, local area networks, wide area networks,

metropolitan area networks, and information service stations (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41).

As per claim 76, Jones discloses mobile internetwork, comprising:

- means for coupling a plurality of network elements including at least one node and at least one local area network among at least one peripheral electronic device (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41);
- means for manipulating node information including configuration and security information (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41);
- means for automatically assembling and configuring the plurality of network elements in response to the node information (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41);
- means for remotely controlling at least one function of the plurality of network elements (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41);
- means for providing secure interoperability among the plurality of network elements in response to the node information (abstract, col. 2, lines 1-25, col. 4, lines 49-67, col. 5, lines 1-54, col. 6, lines 1-16, col. 17, line 67, col. 18, lines 1-55 and col. 19, lines 15-41); and

- wherein the means for coupling provides at least one of data processing, data storage, access control, protocol translation, security including service discovery and device authentication and network control (col. 18, lines 17-22 and lines 42-51; Jones discloses that the communication apparatus can also be configured as a gateway to provide data logging/reduction, vehicle diagnostics, etc. Therefore, Jones does disclose a gateway node that provides at least one of data processing, data storage, access control, protocol translation, security including service discovery and device authentication and network control), wherein the means for coupling controls remote access to the mobile internetwork in response to intermittent external communications (col. 18, lines 42-51).

However, Jones does not explicitly disclose:

- wherein the means for coupling includes at least one interface means, at least one first processing means for performing real-time processing operations and at least one second processing means for performing high level processing operations.

In an analogous art, Lu discloses a cellular private branch exchanges for facilitating cellular communications comprising:

- wherein the means for coupling includes at least one interface means, at least one first processing means for performing real-time processing operations and at least one second processing means for performing high level processing operations (col. 20, lines 50-62 and col. 21, lines 44-60).

Given the teaching of LU, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Jones by including a real-time processor to process real-time information and communicate control information over a VEM bus thereby providing a

system capable of providing and processing real-time information in a timely and efficient manner.

As per claim 78, Jones discloses wherein:

- data is collected by the gateway node using the at least one interface port (col. 18, lines 42-51).

However, Jones does not explicitly disclose:

- the at least one RTIP performs processing to route the data to one of the plurality of network elements.

In an analogous art, Lu discloses a cellular private branch exchanges for facilitating cellular communications comprising:

- the at least one RTIP performs processing to route the data to one of the plurality of network elements (col. 20, lines 50-62 and col. 21, lines 44-60).

Given the teaching of Lu, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Jones by including a real-time processor to process real-time information and communicate control information over a VEM bus thereby providing a system capable of providing and processing real-time information in a timely and efficient manner.

As per claim 79, Jones discloses:

- wherein the at least one interface port is configured to interface with at least one communication physical layer (col. 18, lines 42-51).

As per claim 80, Jones discloses the invention substantially as claims discussed above.

However, Jones does not explicitly disclose:

Art Unit: 2157

- wherein the at least one RTIP further routes communications received at the least one interface port to the at least one application processor.

In an analogous art, Lu discloses a cellular private branch exchanges for facilitating cellular communications comprising:

- wherein the at least one RTIP further routes communications received at the least one interface port to the at least one application processor (col. 20, lines 50-62 and col. 21, lines 44-60).

Given the teaching of Lu, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Jones by including a real-time processor to process real-time information and communicate control information over a VEM bus thereby providing a system capable of providing and processing real-time information in a timely and efficient manner.

As per claim **81**, Jones discloses:

- a bus coupled to the gateway node through the at least one interface port (col. 18, lines 42-51).

However, Jones does not explicitly disclose:

- wherein the at least one application processor hosts an application associated with the bus.

In an analogous art, Lu discloses a cellular private branch exchanges for facilitating cellular communications comprising:

- wherein the at least one application processor hosts an application associated with the bus (col. 20, lines 50-62 and col. 21, lines 44-60).

Given the teaching of Lu, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Jones by including a real-time processor to process real-time information and communicate control information over a VEM bus thereby providing a system capable of providing and processing real-time information in a timely and efficient manner.

As per claim **82**, Jones discloses wherein:

- data is collected by the gateway node using the at least one interface port (col. 18, lines 42-51).

However, Jones does not explicitly disclose:

- the at least one RTIP performs processing to route the data to one of the plurality of network elements.

In an analogous art, Lu discloses a cellular private branch exchanges for facilitating cellular communications comprising:

- the at least one RTIP performs processing to route the data to one of the plurality of network elements (col. 20, lines 50-62 and col. 21, lines 44-60).

Given the teaching of Lu, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Jones by including a real-time processor to process real-time information and communicate control information over a VEM bus thereby providing a system capable of providing and processing real-time information in a timely and efficient manner.

As per claim **83**, Jones discloses the invention substantially as claims discussed above.

However, Jones does not explicitly disclose:

Art Unit: 2157

- wherein the at least one application processor is operable to access raw data from the at least one RTIP.

In an analogous art, Lu discloses a cellular private branch exchanges for facilitating cellular communications comprising:

- wherein the at least one application processor is operable to access raw data from the at least one RTIP (col. 20, lines 50-62 and col. 21, lines 44-60).

Given the teaching of Lu, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Jones by including a real-time processor to process real-time information and communicate control information over a VEM bus thereby providing a system capable of providing and processing real-time information in a timely and efficient manner.

As per claim **84**, Jones discloses the invention substantially as claims discussed above.

However, Jones does not explicitly disclose:

- wherein the real-time operations of the at least one RTIP run below an operating system executed on the at least one application processor.

In an analogous art, Lu discloses a cellular private branch exchanges for facilitating cellular communications comprising:

- wherein the real-time operations of the at least one RTIP run below an operating system executed on the at least one application processor (col. 20, lines 50-62 and col. 21, lines 44-60).

Given the teaching of Lu, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Jones by including a real-time processor to process

Art Unit: 2157

real-time information and communicate control information over a VEM bus thereby providing a system capable of providing and processing real-time information in a timely and efficient manner.

Response to Arguments

3. Applicant's arguments filed October 25, 2006 have been fully considered but they are not persuasive.

The Office Notes the following arguments:

a. Applicants argue that Jones in view of Lu does not teach at least one real-time interface processor (RTIP), and at least one application processor, wherein the at least one RTIP performs real-time operations and the at least one application processor performs high level processing functions.

In response to:

a. Applicants argue that Lu does not teach at least one real-time interface processor (RTIP), and at least one application processor, wherein the at least one RTIP performs real-time operations and the at least one application processor performs high level processing functions. However, the Examiner disagrees. Lu teaches a cellular private branch exchange for facilitating cellular communications for a first plurality of mobile station units in which a real time processor is coupled to a bus to facilitate/perform processing (col. 20, lines 50-62 and col. 21, lines 44-60). By giving the broadest interpretation of Applicants claim language, Jones in view of Lu does teach at least one real-time interface processor (RTIP), and at least one application processor,

Art Unit: 2157

wherein the at least one RTIP performs real-time operations and the at least one application processor performs high level processing functions.

Conclusion

4. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a).

Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to LaShonda T. Jacobs whose telephone number is 571-272-4004.

The examiner can normally be reached on 8:30 A.M.-5:00 P.M..


If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Ario Etienne can be reached on 571-272-4001. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2157

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

ltj
January 16, 2007

LaShonda T Jacobs
Examiner
Art Unit 2157


ARIO ETIENNE
SUPERVISORY PATENT EXAMINER
EBC CENTER 2100